1. (Currently amended) A wireless terminal comprising:

an antenna:

a first visual indicator that indicates begins providing a visual indication to a user of said wireless terminal when a radio is begins transmitting; and

a signal lead for carrying an RF signal from said radio to said antenna and from said antenna to said radio and for carrying a first baseband signal from said radio to said first visual indicator for activating said first visual indicator.

- 2. (Original) The wireless terminal of claim 1 further comprising said radio.
- (Original) The wireless terminal of claim 2 wherein said radio is integral to a PC radio card.
- (Original) The wireless terminal of claim 1 wherein said signal lead is connected to said radio by a detachable connector.
- 5. (Original) The wireless terminal of claim 1 further comprising a second visual indicator that indicates when said radio is receiving and wherein said signal lead also carries a second baseband signal from said radio to said second visual indicator.

- 6. (Currently amended) A wireless terminal comprising:
- an antenna:
- a first visual indicator that indicates begins providing a visual indication to a user of said wireless terminal when a radio is begins receiving: and
- a signal lead for carrying an RF signal from said radio to said antenna and from said antenna to said radio and for carrying a first baseband signal from said radio to said first visual indicator for activating said first visual indicator.
 - 7. (Original) The wireless terminal of claim 6 further comprising said radio.
- (Original) The wireless terminal of claim 7 wherein said radio is integral to a PC radio card.
- (Original) The wireless terminal of claim 6 wherein said signal lead is connected to said radio by a detachable connector.
- 10. (Original) The wireless terminal of claim 6 further comprising a second visual indicator that indicates when said radio is transmitting and wherein said signal lead also carries a second baseband signal from said radio to said second visual indicator.

11. (Currently amended) A wireless terminal comprising:

a radio;

an antenna;

a first visual indicator that indicates to a user of said wireless terminal when said radio is operating; and

a cable that is detachably connected to said radio and that is also connected to said antenna for carrying an RF signal and for carrying a baseband signal from said radio to said first visual indicator:

wherein said first visual indicator indicates when said radio is begins receiving and further comprising a second visual indicator that indicates when said radio is begins transmitting and wherein said cable also carries a second baseband signal from said radio to said second visual indicator.